


Reinforced Asbestos Composite Sheet



Description:

KINGLAND SOLUTIONS Reinforced asbestos composite sheet is combining asbestos gasket material with tang perforated(or flat) steel core(Tinplate/SS304/SS316). It has excellent sealing performance for motorcycle and automobile cylinder ,and could be coated by graphite . The short duration maximum temperature is up to 400°C (750°F).

Composite Type:

KL-S/A. Asbestos fiber sheet + Steel +Asbestos fiber sheet

KL-S/B Asbestos fiber sheet + Steel+ Asbestos fiber sheet +Steel + Asbestos fiber sheet

KL-S/C Steel+ Asbestos fiber sheet

KL-S/D Steel+ Asbestos fiber sheet + Steel

Typical Application:

- > Mainly applied in automobile farming machines, motorcycle and engineering etc.
- > Can be used in high strength gaskets and cylinder gaskets etc.

Prime Features:

- > 100% not including asbestos
- > Excellent performance dilatibility, sealing equality and long life.

Technical Specifications:

Property		Specification
Density g/cm ³		2--3
Compressibility ≥%		8--18
Recovery ≥%		40
Fluid Resistance (At ASTM IRM 903 Oil ,149±2°C,5h)	Weight Change ‰	30
	Thickness Change‰	20
Fluid Resistance (At ASTM IRM 903 Oil ,149±2°C,6h)	Weight Change ‰	30
	Thickness Change‰	20

Standard Sheet Size:

512*1020mm;500*1000mm;500*1200mm;500*1500mm

Thickness:1.0mm ~ 3.0mm

Color: Gray, Black.

The other size is optional or according to the requirements of customers.



TAIZHOU KINGLAND SEALING MATERIALS CO.,LTD

No.8,Lunjiang Road ,Dalun Industrial Zone,Jiangyan ,Taizhou ,Jiangsu ,P.R.China 225504

Tel:+86-523-88342320

Fax:+86-523-88324508

E-mail:info@kinglandsolutions.com

<http://www.kinglandsolutions.com>