

Asbestos latex sheet



Description:

It is made from synthetic latex, asbestos fiber and filling material. Normal used for automobile, agricultural machinery, motorcycle, engineering machinery etc., suitable for lubricating oil under temperature 200°C, usually it will be compounded with tinplate to asbestos composite sheet.

Vulcanized Asbestos latex sheet, it is by vulcanizing, it has smooth face and high density, it can be cut into all kinds of gasket directly.

APPLICATION & PARAMETER:

Gasket materials for explosion engine cylinder gaskets and chemical gaskets

Suitable to sealing lubricating oil at highest temperature 200°C

Technical Data:

| Item | | Style | |
|---------------------------------|-------------------|-------------------------------|--|
| | | KINGLAND Asbestos Latex Sheet | KINGLAND Vulcanized Asbestos Latex Sheet |
| Density | g/cm ³ | 1.0~1.1 | 1.3~1.4 |
| Tensile strength | ≥Mpa | 6 | 13 |
| Compressibility | ≥% | 20±5 | 20±5 |
| Recovery | ≥% | 35 | 40 |
| Stress relaxation | ≤% | 30 | 30 |
| In 20# aviation oil, 150°C, 5h | Oil absorption ≤ | 32% | 32% |
| | Thick increases ≤ | 12% | 12% |
| In 75# aviation oil 15~30°C, 5h | Oil absorption ≤ | 30% | 30% |
| | Thick increases ≤ | 20% | 20% |

Normal color: Grey, Black,

| Item | Tolerance | In same sheet |
|-----------|-----------|---------------|
| Thickness | ±mm | mm |
| 0.5mm | 0.05 | 0.06 |
| 0.6-0.8mm | 0.06 | 0.08 |
| 1--2mm | 0.08 | 0.08 |

Dimensions:

Thickness: 0.4~2.0mm

500x1500mm; 500x1000mm; 500x500mm; 500x1200mm; 1000x1500mm; 1000x1200mm;



TAIZHOU KINGLAND SEALING MATERIALS CO.,LTD

No.8,Lunjiang Road ,Dalun Industrial Zone,Jiangyan ,Taizhou ,Jiangsu ,P.R.China 225504

Tel:+86-523-88342320

Fax:+86-523-88324508

E-mail:info@kinglandsolutions.com

<http://www.kinglandsolutions.com>