

Asbestos Rubber sheet



Description:

KINGLAND SOLUTIONS Asbestos Rubber Sheet is made from asbestos fiber, rubber and heat-resisting materials, compressing it into thick paper.

Typical Application:

- > Used for equipment in water, steam, etc.
- > Used as sealing material in the joint of pipeline

Prime Features:

- > Economical sheet
- > Wide range of pressure and temperature

Technical Data:

KINGLAND Asbestos Rubber Sheets						
GB/T539-1995						
Item	KLXB450	KLXB400	KLXB350	KLXB300	KLXB200	KLXB150
Tensile strength MPa \geq	19	15	12	9	6	5
Aging Coefficient \geq	0.9					
Burning Loss % \leq	28		30		30	
Density g/cm 3	1.6 — 2.0					
Compressibility %	12 \pm 5					
Rebound degree	45		40		35	
Pliability	No Crack					
Stress-relaxation \leq	50					
Steam Airtightness	with the temperature of 440-450 $^{\circ}$ C and the pressure of 11-12MPa,Keep for 30 min without puncture	with the temperature of 390-400 $^{\circ}$ C and the pressure of 8-9 MPa,Keep for 30 min without puncture	with the temperature of 340-350 $^{\circ}$ C and the pressure of 7-8 Mpa,Keep for 30 min without puncture	with the temperature of 290-300 $^{\circ}$ C and the pressure of 4-5 MPa,Keep for 30 min without puncture	with the temperature of 200-220 $^{\circ}$ C and the pressure of 2-3 Mpa,Keep for 30 min without puncture	with the temperature of 140-150 $^{\circ}$ C and the pressure of 1.5-2 MPa,Keep for 30 min without puncture

Dimensions:

- 4100 x 1500 x (0.5 – 6.0)mm, 2000 x 1500 x (0.5 – 6.0)mm,
 1500 x 1360 x (0.5 – 6.0)mm, 3810 x 1270 x (0.5 – 6.0)mm
 1270 x 1270 x (0.5 – 6.0)mm, 1500 x 1500 x (0.5 – 6.0)mm

The other size is optional or according to the requirements of customers.

Packing: In wooden pallet of about 1000 kgs, 2000kgs net each.



TAIZHOU KINGLAND SEALING MATERIALS CO.,LTD

No.8,Lunjiang Road ,Dalun Industrial Zone,Jiangyan ,Taizhou ,Jiangsu ,P.R.China 225504

Tel:+86-523-88342320

Fax:+86-523-88324508

E-mail:info@kinglandsolutions.com

<http://www.kinglandsolutions.com>