

Oil resisting asbestos rubber sheet



Description:

KINGLAND SOLUTIONS Oil resisting asbestos rubber sheets are made from good long asbestos fiber, oil-resistant synthetic rubber, heat resisting material compound heating and compression molding. It used as sealing material in the joint of oil pipeline and sealing gaskets.

Typical Application:

- > Used for equipment in water, steam, etc.
- > Used as sealing material in the joint of pipeline, automobiles motorcycles, etc

Prime Features:

- > Wide range of pressure and temperature

Technical Data:

KINGLAND Oil resisting Asbestos Rubber Sheet					
GB/T539-1995					
Item		KLNY400	KLNY300	KLNY250	KLNY150
With the temperature of 150+/-20C, dipped in No.20 aviation oil for 5h, then	Horizontal strain \geq Mpa	26	10.8	9	8
	Oil absorptivity \leq	9	23	23	23
	Thickness increasing \leq %	15	15	20	
	Change of outlook	No bubble			
With the temperature of 15~30 °C, dipped in No.75 aviation gasoline for 5h, then take out and laid for 5min	Horizontal Strain \geq Mpa	14.7	7.9	7	6
	Oil Absorptivity \leq %	15	22	22	22
	Thickness increasing \leq %	20	25	25	
	Softness	No crack			
	Softness	No crack			
	Density g/cm3	1.6~2.0			
	Compressibility %	12+/-5			
	Elasticity \geq	50	45	45	35
Oil-sealing	Temperature 15~30oC medium: No#75 aviation gasoline or No#3 jet fuel	Pressure: 12Mpa	Pressure: 15Mpa	Pressure: 10Mpa	Pressure: 8Mpa
Corrosivity	Hard aluminium plate, low carbon steel	No corrosion			
	Horizontal strain \geq Mpa		12.7	11	9
	Stress relaxation \leq %	45			

Dimensions:

4100x1500x(0.5~6.0)mm, 2000x1500x(0.5~6.0)mm

1500x1360x(0.5~6.0)mm, 3810x1270x(0.5~6.0)mm

1270x1270x(0.5~6.0)mm, 1500x1500x(0.5~6.0)mm

The other size is optional or according to the requirements of customers.



TAIZHOU KINGLAND SEALING MATERIALS CO.,LTD

No.8,Lunjiang Road ,Dalun Industrial Zone,Jiangyan ,Taizhou ,Jiangsu ,P.R.China 225504

Tel:+86-523-88342320

Fax:+86-523-88324508

E-mail:info@kinglandsolutions.com

<http://www.kinglandsolutions.com>