

Spun Kevlar Packing



Description:

Aramid fiber packing is braided from high quality Dupont kevlar fiber with PTFE impregnated and lubricant additive. It shows good chemical resistance, high elasticity and very low cold flow. It can resist severe media and higher pressure. The packing is lubricated with silicone based compound for quick and easy break-in.

Typical Application:

- > This is a universal packing which can be used for pumps in all types of industry.
- > Chemical, petrochemical, pharmaceutical, food and sugar industries, pulp and paper mills, etc.
- > A durable packing able to withstand granular and abrasive applications.

Prime Features:

- > For hot water application it can be used uncooled up to 160 °C.
- > It can be used as stand-alone packing also combined with others as anti-extrusion ring.
- > Superior performance
- > Lower frictional factor

Technical Data:

Material		Dupont kevlar fiber with PTFE impregnated and lubricant additive
Temperature Range		-100 up to +280 °C
Process	Rotating	25 bar
	Reciprocating	100 bar
	Static	250 bar
Shaft Speed		25m/s
PH		2~12
Density		Appr. 1.4g/cm ³



TAIZHOU KINGLAND SEALING MATERIALS CO.,LTD

No.8,Lunjiang Road ,Dalun Industrial Zone,Jiangyan ,Taizhou ,Jiangsu ,P.R.China 225504

Tel:+86-523-88342320

Fax:+86-523-88324508

E-mail:info@kinglandsolutions.com

<http://www.kinglandsolutions.com>