

Carbon Fiber Packing



Description:

Carbon fiber packing braided from strong carbon continuous yarns after softening, impregnated with proprietary lubricants and graphite particles, with fill voids, act as a break-in lubricant, and block leakage

Typical Application:

- > Used for stuffing boxes of pumps or valves
- > Be used as anti-extrusion ring
- > Handle water, steam, acids and alkalis for power stations, boiler plants, etc.

Prime Features:

- > High pressure and high temperature application
- > Perfect seal for dry-running equipments like ventilators and fans
- > Seats quickly, break-in without extensive adjustments.

Technical Data:

Material	100% carbon fiber yarns	
Temperature Range	-50 up to +650 °C atmosphere;	
Process	Rotating	25 bar
	Reciprocating	100 bar
	Static	200 bar
Shaft Speed	20m/s in rotary	
PH	2~12	
Density	1.2~1.4g/cm ³	



TAIZHOU KINGLAND SEALING MATERIALS CO.,LTD

No.8,Lunjiang Road ,Dalun Industrial Zone,Jiangyan ,Taizhou ,Jiangsu ,P.R.China 225504

Tel:+86-523-88342320

Fax:+86-523-88324508

E-mail:info@kinglandsolutions.com

<http://www.kinglandsolutions.com>