Pure PTFE Packing with Oil



Description:

Pure PTFE Packing with Oil braided from pure PTFE yarn which impregnated with silicone oil. It is designed for dynamic condition. The oil can reduce the frictional factor.

Typical Application:

> Universal packing suitable for valves, pumps and agitators in most mediums

Prime Features:

- > Clean, non-contaminating and graphite free
- > Long maintenance free service life
- > Minimal shaft wear and leakage
- > Superior performance
- > Lower frictional factor

Technical Data:

| Material Temperature Range | | 100% Pure PTFE yarn with Silicone oil -150 up to +260 °C | |
|-------------------------------|---------------|---|--|
| | | | |
| Process | Rotating | 15 bar | |
| | Reciprocating | 100 bar | |
| | Static | 200 bar | |
| Shaft Speed | | 10m/s | |
| PH | | 0~14 | |
| Density | | 1.6g/cm ³ | |



TAIZHOU KINGLAND SEALING MATERIALS CO.,LTD

No.8,Lunjiang Road ,Dalun Industrial Zone,Jiangyan ,Taizhou ,Jiangsu ,P.R.China 225504
Tel:+86-523-88342320Fax:+86-523-88342320E-mail:info@kinglandsolutions.comhttp://www.kinglandsolutions.com