

Acrylic Fiber Packing



Description:

Acrylic fiber packing braided from high strength acrylic fiber with PTFE impregnated twice time. It has excellent properties of sealing, lubricating and resistant to chemical. The acrylic packing can be with or without oil. High elastic red silicone rubber core can absorb vibration.

Typical Application:

- >Wide variety of uses throughout a plant
- > Pumps and valves, and can handle more chemicals except strong acid, strong alkali and strong oxidizer

Prime Features:

- > Especially for the condition of middle temperature. High pressure, high speed,.
- > Has excellent properties of sealing, lubricating and resistance to chemicals

Technical Data:

Material		100% Acrylic fiber and PTFE
Temperature Range		-50 up to +260 °C atmosphere;
Process	Rotating	20 bar
	Reciprocating	80 bar
	Static	100 bar
Shaft Speed		20m/s in rotary
PH		1~13
Density		1.3 g/cm ³



TAIZHOU KINGLAND SEALING MATERIALS CO.,LTD

No.8,Lunjiang Road ,Dalun Industrial Zone,Jiangyan ,Taizhou ,Jiangsu ,P.R.China 225504

Tel:+86-523-88342320

Fax:+86-523-88324508

E-mail:info@kinglandsolutions.com

<http://www.kinglandsolutions.com>