


Knolly Fiber Packing



Description:

Braided from high-performance Kynol™ (Novolid™ or Phenolic™) fiber impregnated with PTFE lubricant, good mechanical properties combining softness and strength.

We call it "GOLDEN Packing".

Typical Application:

- > High performance packing that is well suited to applications where graphite impregnation may not be acceptable.
- > Suitable for abrasive media, and where contamination is not permitted.
- > Used in chemical plants and pulp and paper mills, rotating and reciprocating pumps, washer journals, liquor pumps, refiners.

Prime Features:

- > High dimensional stability and superior pressure resistance even at elevated temperature
- > Good process-ability, easy to cut and fit
- > Thermal stability, low heat expansion
- > Outstanding chemical resistance particularly in acidic media
- > Excellent resistance to organic solvents, oil and fuels

Technical Data:

Material		100% Kynol fiber and PTFE
Temperature Range		-200 up to +260 °C atmosphere;
Process	Rotating	20 bar
	Reciprocating	100 bar
	Static	200 bar
Shaft Speed		20m/s in rotary
PH		1~13
Density		1.5 g/cm ³



TAIZHOU KINGLAND SEALING MATERIALS CO.,LTD

No.8,Lunjiang Road ,Dalun Industrial Zone,Jiangyan ,Taizhou ,Jiangsu ,P.R.China 225504

Tel:+86-523-88342320

Fax:+86-523-88324508

E-mail:info@kinglandsolutions.com

<http://www.kinglandsolutions.com>